FEDERAL SPECIFICATION

PADLOCK, CHANGEABLE COMBINATION (RESISTANCE TO OPENING BY MANIPULATION AND SURREPTITIOUS ATTACK)

This amendment, which forms a part of FF-P-110G, dated December 31, 1987 is approved for use by all Departments and Agencies of the Civil Government and the Department of Defense.

Page 2

Paragraph 3.13.2.1, line 5

DELETE:

"with 0.094 inch die prior"

SUBSTITUTE: "with a die in the range of 0.09375 thru 0.130 inches prior"

Paragraph 3.13.2.2, line 4

DELETE:

"with a 0.094 inch die prior"

SUBSTITUTE: "with a die in the range of 0.09375 thru 0.130 inches prior"

|Beneficial comments (recommendations, additions, deletions) and any pertinent | data which may be of use in improving this document should be addressed to: | |Commanding Officer (Code 156), Naval Construction Battalion Center, Port | |Hueneme, CA 93043-5000, by using the self-addressed Standardization | |Document Improvement Proposal (DD Form 1426) appearing at the end of this | |document or by letter.

FSC 5340

<u>DISTRIBUTION STATEMENT A</u>. Approved for public release; distribution is unlimited.

U. S. GOVERNMENT PRINTING OFFICE: 1990 - 262-854/08544